


HAZARD RATING
 4-EXTREME
 3-HIGH
 2-MODERATE
 1-SLIGHT
 0-INSIGNIFICANT



MATERIAL SAFETY DATA SHEET

(Prepared according to 29 CFR 1910.1200)

Date Prepared: 3-1-10

SECTION 1 - PRODUCT IDENTIFICATION

Company Name	Rocket Industrial, Inc.	Emergency Telephone No.	1-800-535-5053
Address	8101 International Drive, Wausau, WI 54402	Information Telephone No.	1-800-826-4405
Product Name / ID#	Unreal Spot Care Encapsulation (3104)	Product Type	Spotter <input checked="" type="checkbox"/> Proprietary Product

SECTION 2 - HAZARDOUS INGREDIENTS

Chemical Name/Common Name	Cas No.	Percent (optional)	TLV (Source)
Dipropylene Glycol Methyl Ether	34590-94-8	< 5%	25 ppm (skin)
Isopropyl Alcohol	67-63-0	< 5%	400 ppm (ACGIH)

* Substances Contains no substances - subject to the reporting requirements of SARA 313 and 40 CFR Part 372.

SECTION 3 - PHYSICAL DATA

Boiling Point (°F)	212°F	Specific Gravity (H ₂ O=1.0)	1.0 ± 0.005	pH	8.0 ± 0.5	% VOC (ww)	6.2%
Solubility In Water	<input checked="" type="checkbox"/> Complete <input type="checkbox"/> Insoluble <input type="checkbox"/> Emulsifiable or (Dispersible) <input type="checkbox"/> Slight (or Partial)						
Evaporation Rate (vs H ₂ O)	Unknown <input type="checkbox"/> Faster <input type="checkbox"/> Slower <input checked="" type="checkbox"/> About the Same	Vapor Pressure	NE	Vapor Density	NE		

Appearance and Odor Clear amber, thin liquid. Floral scent.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point (T.C.C.)	> 100°F	<input type="checkbox"/> None to boiling	Flammable Limits	Upper	NE	Lower	NE
Extinguishing Media	CO ₂ , Dry Chemical, Water fog						
Special Fire Fighting Procedures	NA						
Unusual Fire Explosion Hazards	NA						

SECTION 5 - REACTIVE DATA

Stability Stable Incompatibility Oxidizing material.

Hazardous Decomposition Products Oxides of carbon.

SECTION 6 - HEALTH HAZARDS

Threshold Limit Value Product See Section 2 for Ingredients TLV None Established Not Applicable Primary routes of Exposure Eyes Skin Oral Inhalation

Signs Symptoms of Over-exposure (Acute) May cause eye and skin irritation. Possible harmful absorption through skin. Excessive inhalation may cause irritation of the respiratory tract, headache or dizziness. Gastro intestinal irritation if swallowed.

Signs Symptoms of Over-exposure (Chronic) May be harmful if absorbed through skin.

Medical Conditions Aggravated by Over-exposure Unknown

Carcinogen/Suspected Carcinogen Ingredients: NTP IARC OSHA None

SECTION 7 - FIRST AID PROCEDURES - (If any Condition persists - Consult a physician.)

Eyes Flush with water for 15 minutes.

Skin Flush with water for 15 minutes.

Ingestion Give quantities of water to dilute contents in stomach. Induce vomiting only as directed by a doctor. Get medical attention.

Inhalation Remove victim to fresh air. If qualified, give oxygen or artificial respiration if breathing is difficult or as needed.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection None

Ventilation requirements Local Exhaust Mechanical As needed to keep below any listed TLV or for general good ventilation.

Protective Gloves Rubber gloves, if prolonged contact Eye Protection Safety glasses

Other Protective Clothing Chemical apron when handling large volumes or when splashing is anticipated.

SECTION 9 - SPILL OR LEAK PROCEDURES

Steps to be Taken if Released or Spilled Contain spill. Mop up, rinse with water.

Waste Disposal Methods Flush into sanitary sewer system in accordance with federal, state and local regulations.

SECTION 10 - STORAGE AND HANDLING INFORMATION

Precautions to be Taken in handling and Storage Observe personal hygiene. Store so as to be inaccessible to children.